

3 Megapixel Day & Night Vandal Dome Network Camera

VD-300Ap V5


HDTV 1080p/720p • 3M/2M/1.3M Resolution Supported





- 3 Megapixel High Resolution Outdoor Vandal Dome Camera
- **SmartFocus**® to Ease the Zoom and Focus Adjustment Remotely
- HDTV Quality (Full HD 1080p @ 30fps Streaming)
- MPEG-4, MJPEG and H.264 Triple Codec Compression
- **Intelligent Multi-Profile Sensor Management**® for Different Environments
- Removable IR-cut Filter /Auto Light Sensor for Day and Night
- 1 DI/DO for External Alarm and Sensor Device
- 3 Axis design
- Two-way Audio/Built-in SD/SDHC/SDXC Memory Card Slot for Local Storage
- IK10 Vandal Proof and IP67 Weather Proof Outdoor Enclosure
- Power over Ethernet/DC 12V/AC 24V support
- Smart IR to adjust the IR LED light across the entire area to get a well illuminated image



Photo Indication & Dimension Diagram



- | | |
|--|--|
| ① Fan | ⑧ Terminal Block
(For Audio in/out, DIDO) |
| ② LEDs | ⑨ TV Out Connector |
| ③ RJ45 Connector
(For Ethernet and 802.3 at PoE Plus) | ⑩ Terminal Block (For
DC12V/AC24V) |
| ④ Conduit Plug and Hole | ⑪ SD Card Slot |
| ⑤ LENS | |
| ⑥ Tilt Screw | |
| ⑦ Reset Button | |



Camera		Events and Alarm Management	
Models	3M, Motorized Lens, SmartFocus®	Events	Motion Detection/ Schedule/ Audio Detection/ Digital Input/ Temperature Alarm/ Auto Focus Shift for Day & Night
Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR	Alarm	Stream/Snapshot to FTP/Email/Samba/SD-Card HTTP/Email Notification/ Digital Output
Image Sensor	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution :2048x1536 pixel	Audio	
Minimum Illumination	0 lux (IR ON, B/W) 0.01lux (IR OFF, B/W) 0.02 lux (F1.4, Color)	Audio Streaming	2-way Audio Support
IR Illuminators	Built -in IR Illuminators, effective up to 25 meters IR LED: 20pcs IR wavelength: 850nm	Audio Compression	G.711, AMR (8 kHz, Mono, PCM)
Lens	Lens Type: Board Lens F No.: 1.4 Focal Length: f= 3.3mm(W)~10.5mm(T) View Angle(Normal Mode): (H): 68°~26°/ (V): 50°~20°/ (D):86°~32° View Angle(Ultra Wide Mode): (H): 86°~33°/ (V): 64°~22°/ (D):112°~41°	Audio Input/ Output	Line In/ Out
Day & Night ICR	Triggered by Light sensor, Scheduling, Digital Input	General	
Local Storage	Built-in SD/SDHC/SDXC Max.64G Memory Card Slot	Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv6
Video		Power Input/ Operating Temperature	802.3 af POE/ DC12V 1A /AC 24V: -20°C ~ 60°C (-4°F ~140°F) 802.3at PoE Plus(build in fan and heater): -40°C ~ 60°C (-40°F ~140°F)
Compression Streaming	H.264 / MPEG4 / MJPEG Simultaneous multiple streams	Max. Power Consumption	DC12V 1.5A/AC 24V: 12.5 Watts 802.3 af POE:15 Watts 802.3 at POE Plus:27.5 Watts
Video Setting	Multi-Profile Image Management: Day/ Night/ Sunset/ User 1/ User 2 Auto Exposure Control Manual Exposure Control: 1/20000~1/5s Manual Gain Control: 1X ~ 32X Manual White Balance Control: 2000K~7000K	Environment	Water Proof: IP67 Operating Humidity : 10% ~ 80%
S/N Ratio	38.1 dB	Dimension	113.75 (D) mm X 144.25(H) mm
Image Resolution	3M : 2048x1536 @ 18fps 2M (Full HD) : 1920x1080 @30fps 1M : 1280x720 @ 30fps	Weight	860g/1.90lb
		Housing	Weather-proof (IP67) Vandal-proof (IK10)
		Certification	FCC, CE, IK10
		Viewing System Requirements	OS: Microsoft Windows 8/7/Vista/XP/2000 Browser: Mozilla Firefox, Internet Explorer 7/8 or above, Safari, Google Chrome Cell Phone: 3GPP player Real Player: 10.5 or above Quick Time: 6.6 or above VLC
		Warranty	Limited 3-year warranty

Work Best With

Camera Accessories Options



L-WM-01
Camera Bracket



POE30U *
High Power PoE Injector



WPC *
Waterproof Connector

Network Equipment Options



PS-588I-v2
8-port 10/100M PoE Fast Ethernet Switch



PS-7242IL-AT
24-port 10/ 100M High Power PoE+ Web Smart Ethernet Switch